



the future is safer with altro


altro

# Altro Aquarius™


Safety Flooring / Suelos de Seguridad / Sicherheitsbodenbelag

**NEW**  
wet & dry, any  
shoe & barefoot use


Altro is the first safety  
flooring manufacturer to  
recycle traditional safety  
flooring in-house




Dragonfly AQ2001  
WR292 / A1M292 / LRV 33




Blue Penguin AQI2002  
WR288 / A1M71 / LRV 24




Treefrog AQI2003  
WR293 / A1M271 / LRV 33




Cygnet AQ2004  
WR287 / A1M79 / LRV 46




Puffin AQI2005  
WR287 / A1M79 / LRV 46




Terrapin AQI2009  
WR289 / A1M265 / LRV 40




Walrus AQ2007  
WR261 / A1M81 / LRV 29




Tern AQI2008  
WR261 / A1M81 / LRV 31




Otter AQI2006  
WR290 / A1M239 / LRV 26



Vole AQ2010  
WR289 / A1M265 / LRV 43



Salamander AQI2011  
WR294 / A1M294 / LRV 51



Swan AQI2012  
WR291 / A1M1 / LRV 75

Altro Whiterock™ wall cladding is the perfect complement in wet areas, for details visit [www.altro.com](http://www.altro.com).

Exact material match with samples cannot be guaranteed.

No podemos garantizar que el material del suelo de seguridad coincida exactamente con el de las muestras.

Eine exakte Übereinstimmung des Materials mit Mustern kann nicht garantiert werden.

A+ BRE Generic Green Guide  
Rating for Safety Flooring, full  
details available at  
[www.thegreenguide.org.uk](http://www.thegreenguide.org.uk)



Flooring Type Tipo de pavimento Belagsart		EN 13845/ EN 13553	Safety flooring Suelo de seguridad antideslizante Sicherheitsbodenbelag
Classification for use Areas de uso Einsatzbereiche		EN 685	34 & 43 34 y 43 34 & 43
Slip Resistance Resistencia al deslizamiento Rutschsicherheit		TRRL EN 13845 EN 13893 DIN 51130 / DIN51097 CTE	≥ 36 Esf / ESb DS R10 / Class B Clase 3
Thickness Espesor Total Gesamtdicke		EN 428	2 mm
Flexibility Flexibilidad Flexibilität		EN 435	Pass Conforme bestanden
Wear Layer Capa de uso Nutzschicht		EN 429	2 mm
Weight Peso Flächengewicht		EN 430	2.4 kg/m <sup>2</sup>
Roll Dimensions Dimensiones del rollos Rollenabmessungen		EN 426	2 m x 20 m = 40 m <sup>2</sup>
Light Fastness Resistencia a la luz Lichtechtheit		EN 20105-B02	≥ 6
Sound Insulation Aislamiento acústico Trittschal		ISO 140-8	5 dB (subject to validation)
Wear Resistance Abrasión Verschleißverhalten		EN 13845	<10% particles lost over 50000 Cycles <10% de las partículas perdidas en 50.000 ciclos <10% Partikel wurden über 50000 Umdrehungen verloren
Indentation Punzonamiento Resteindruck		EN 433	≤ 0.10mm
Fire Performance Reacción al fuego Brandverhalten		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl s1 ≥ 8kW/m <sup>2</sup> Pass Clase Bfl s1 ≥ 8kW/m <sup>2</sup> Conforme Klasse Bfl-s1 ≥ 8kW/m <sup>2</sup> , bestanden
Chemical Resistance Resistencia a los productos químicos Chemikalieneinwirkung**		EN 423	Good Buena beständig
Castor Chair Abrasion Huellas de sillas de ruedas Stuhlrollenbeanspruchung		EN 425	Pass Conforme geeignet
Under floor heating Calefacción por el suelo Fußbodenheizung		EN 12667	Suitable Apto geeignet
Electrical Behaviours Características eléctricas Elektrisches Verhalten		EN 1815	≤ 2 kV Antistatic ≤ 2 kV Antiestáticas ≤ 2 kV antistatisch
Biocide Bakteriostat Bacteriostático			Contains Integral Biocide Enthält Bakteriostat Contiene agente bacteriostático integral

Please refer to local building regulations/codes of practice.

\*\* Caution Ketone/Aromatic Solvents. Please contact Altro for further technical advice regarding staining and chemical resistance.

### Installation and Maintenance

All Installations in accordance with Altro safety flooring instructions and Local Codes of Practice.

Please refer to Altro Cleaning Card for maintenance advice. Failure to install and maintain Altro

flooring in accordance with installation instructions can affect its performance and slip resistance.

Floors should be protected from other trades and thoroughly cleaned before handover.



Contains recycled material



For further information, Light Reflectance Values, Weld Rod and Mastic codes, please visit [www.altro.com/aquarius](http://www.altro.com/aquarius)

Für weitere Informationen über Lichtreflektionswerte, sowie Artikelnummern für Schweißschnüre und Dichtmasse besuchen Sie uns bitte auf [www.altro.de/aquarius](http://www.altro.de/aquarius)

Para más información sobre el índice de Reflectancia de la Luz, barras de soldadura y mastiques visite [www.altroscandess.com/aquarius](http://www.altroscandess.com/aquarius)